

# TOYO TIRES®

## M-606 OPEN COUNTRY +4™ ALL-SEASON LIGHT TRUCK RADIAL

The M-606 Open Country +4 radial delivers rugged performance with a stable, quiet ride. A versatile performer, the M-606 is well suited for commercial and heavy-duty work trucks.

### Typical Vehicle Matches

Pickups, vans and sport utility vehicles used in demanding commercial/rural applications

### Typical Customer Matches

Value, quality and performance-oriented upgraders from Original Equipment tires

### Competitive Products

- BFGoodrich All-Terrain T/A KO
- Bridgestone Dueler APT III



### WARRANTY

Limited warranty:  
workmanship and  
materials only.

Customer Benefit	Product Features
All-Season Traction	<ul style="list-style-type: none"> <li>• All-season block tread design</li> <li>• Computer-optimized contact patch</li> <li>• Two full-width steel belts</li> <li>• Cap/base tread compound</li> <li>• M&amp;S rated</li> </ul>
All-Purpose Traction	<ul style="list-style-type: none"> <li>• Tough two-ply polyester casing</li> <li>• High bead filler</li> <li>• High-ply turn-up construction</li> <li>• All-season block tread design</li> <li>• Large shoulder blocks</li> </ul>
Comfortable, Quiet Ride	<ul style="list-style-type: none"> <li>• Polyester cord body for smooth ride</li> <li>• Tread designed for minimum noise</li> </ul>
Wet Traction	<ul style="list-style-type: none"> <li>• Three wide tread grooves evacuate water</li> <li>• Special tread rubber compound maximizes grip on wet surfaces</li> <li>• Tread sipes provide extra biting edges</li> </ul>
Long Treadlife	<ul style="list-style-type: none"> <li>• Heavy-duty bead construction</li> <li>• Two full-width steel belts</li> <li>• Cap/base tread compound</li> <li>• Deeper tread depth</li> </ul>

LIGHT TRUCK/SUV

Tire Size	Product Code	Approved Rim Width Range (inch)	Tire Weight (lbs.)	Tread Depth (3/32")	Inflated Dimensions		Static Loaded Radius (inch)	Max. Load (lbs.)		Max. Pressure (PSI)		Revs Per Mile	Price
					O.A.D. (inch)	O.A.W. (inch)		Single	Dual	Single	Dual		
LT235/85R16 119/116M E/10	315120	6.0-6.5-7.0	48	17	31.7	9.3	14.8	3042	2778	80	80	650	
LT245/75R16 120/116M E/10	315400	6.5-7.0-7.5	48	18	30.5	9.8	14.3	3042	2778	80	80	676	

Bold designates measuring rim width.

All Toyo brand tires are subject to continuous development. Toyo Tire U.S.A. Corp. reserves the right to change construction, materials or specifications without notice or obligation. Contact your Toyo dealer or Toyo Tires for current information.