

TOYO TIRES®

M-55™ LIGHT TRUCK ALL-POSITION TRACTION RADIAL

The M-55 is an all-position traction radial designed to deliver versatility and exceptional mileage with dependable traction on- or off-road. Easily handles rough terrain, mud and snow. Built to handle the most demanding commercial applications.

Typical Vehicle Matches

Commercial-use vehicles, functional family pickups, vans and SUVs

Typical Customer Matches

Commercial/agricultural fleet owners/operators and function-oriented buyers looking to upgrade from Original Equipment tires

Competitive Products

- BFGoodrich Commercial T/A Traction
- Firestone Transforce AT
- Goodyear Workhorse Extra Grip
- Michelin XPS Traction

WARRANTY

Limited warranty: workmanship and materials only.



Customer Benefit	Product Features
Solid Handling and Traction	<ul style="list-style-type: none"> • High bead fillers • Aggressive block and lug tread design • Wide tread base • Open shoulder design • Numerous sipes provide more biting edges in the tread • Pinned for studs • M&S rated
Durability	<ul style="list-style-type: none"> • Heavy-duty bead construction • Tough two-ply polyester casing or three-ply depending on size • Wide steel belts • Cap/base tread compound
Long Treadlife	<ul style="list-style-type: none"> • Two-ply polyester casing or three-ply depending on size • Wide steel belts • Computer-optimized tread design • 17-19/32nds tread depth
Smooth, Quiet Ride	<ul style="list-style-type: none"> • Polyester casing • Computer-optimized tread design • Variable tread elements • Advanced casing design absorbs shocks

Tire Size	Product Code	Approved Rim Width Range (inch)	Tire Weight (lbs.)	Tread Depth (% ³²)	Inflated Dimensions		Static Loaded Radius (inch)	Max. Load (lbs.)		Max. Pressure (PSI)		Revs Per Mile	Construction		Price
					O.A.D. (inch)	O.A.W. (inch)		Single	Dual	Single	Dual		Tread	Sidewall	
LT215/75R15 100/97M C/6	309160	5.5-6.0-7.0	31	17	27.7	8.5	13.1	1765	1610	50	50	738	2P+2S+1N	2P	
LT235/75R15 104/101M C/6	309200	6.0-6.5-7.0	35	18	28.9	9.3	13.6	1985	1820	50	50	710	2P+2S+1N	2P	
LT215/85R16 115/112N E/10	309440	5.5-6.0-7.0	43	16	30.7	8.6	14.3	2680	2470	80	80	676	2P+2S	2P	
LT235/85R16 120/116N E/10	309460	6.0-6.5-7.5	49	17	32.0	9.3	14.9	3042	2778	80	80	649	2P+2S+2N	2P	
LT255/85R16 123/120M E/10	309470	6.5-7.0-8.0	56	18	33.3	10.4	14.7	3415	3085	80	80	624	3P+2S	3P	
LT225/75R16 115/112N E/10	309410	6.0-7.0	39	17	29.4	8.5	13.7	2680	2470	80	80	706	2P+2S	2P	
LT245/75R16 120/116N E/10	309420	6.5-7.0-8.0	46	17	30.7	9.8	14.3	3042	2778	80	80	675	2P+2S+2N	2P	
LT265/75R16 123/120N E/10	309430	7.0-7.5-8.0	54	18	31.9	10.8	14.2	3415	3085	80	80	651	3P+2S+2N	3P	
LT285/75R16 126/123M E/10	309180	7.5-8.0-9.0	60	18	33.2	11.3	15.4	3740	3415	80	80	625	3P+2S+2N	3P	
LT235/80R17 120N E/10	309490	6.0-6.5-7.5	49	17	31.9	9.3	14.8	3085		80		651	2P+2S	2P	
LT245/75R17 121N E/10	309500	6.5-7.0-7.5	49	18	31.9	9.7	14.8	3195		80		651	2P+2S	2P	
LT265/70R17 121N E/10	309480	7.0-8.0-8.5	53	18	31.9	10.6	14.8	3195		80		650	2P+2S	2P	
LT275/70R18 125N E/10	309510	7.0-8.0-8.5	57	17	33.6	11.0	15.6	3640		80		618	2P+2S	2P	

Bold designates measuring rim width. All sizes studable. All Toyo brand tires are subject to continuous development. Toyo Tire U.S.A. Corp. reserves the right to change construction, materials or specifications without notice or obligation. Contact your Toyo dealer or Toyo Tires for current information.

LIGHT TRUCK/SUV